



MINI TRUCK RULES 2021

WWW.TRIPLEDENTERTAINMENTLLC.COM

1. Fuel tanks must be replaced with a steel/aluminum fuel cell and located securely in back seat.
2. You may use engine of choice. This means you can run a V8 engine if you would like.
3. A 4-point cage is mandatory with a roll over bar. The cage in the cab may be 4 down legs from front and rear bar straight down to the top of the frame. Protector may attach to the frame but may not extend further than 24" from the front of the bed.
4. Fuel Cell must have a protector around it. The gas tank protector cannot be any larger than 32" OD and no be no further back than 24" from the front of the bed.
5. Batteries must be moved to front floor of cab and be securely fastened to floor and covered.
6. Doors must be secured by wire or welded shut. No loose doors allowed.
7. Tail gates may be welded shut. They may be welded to the bumper on the rear of the truck.
8. Bed seams where the bed sides meet the floor may be welded inside of the bed ONLY. No metal may be added. These welds cannot be any larger than ½" welds.
9. Box & Cab mounts may be replaced with up to 1" bolts.
10. Body mounts may be removed. The body bolts may go all the way through the frame and floor of the truck.
11. No trailer hitches or reinforcements of frame or body of any kind permitted.
12. You may use car bumpers: for mounting of car bumpers, you may use factory bumper shocks and brackets or a 3" x 3" x 5" long box steel or likewise material.
13. Hoods must be in place and operable. Must have a 12" by 12" hole cut in hood over carburetor.
14. Hoods must be wired or bolted shut. Only 8 double strands of wire allowed. All can go to frame or bumper. If bolting down you can bolt down up to 6 places with no larger than ½" bolts.
15. NO 4-Wheel drives allowed. 4-wheel drives must have front drive shaft removed.
16. Bead-locks and rim guards cannot be used. Full centers are allowed as long as inside the rim
 - a. Outer rim must appear stock.
17. Any tire permitted.
18. Any Rear-end of choice will be permitted.
19. Beds must be welded to the cab of the truck with a 3" strap directly behind doors.
20. 8 strands of #9 wire allowed on front and rear of truck all is permitted to go to the frame.
21. Suspension may be solid. Bumpers can be no higher than 22" from bottom of bumper to ground- front & rear.
 - a. Truck must set level.
22. No pulling down rear of the truck. No smashing of the bed sides will be allowed. You must use factory springs for make and model of truck. You may use all thread for shocks.
23. On trucks with out front leaf springs you can have kickers from the dash bar to frame behind A-Arms 2" x 2"x1/4"

EVENT QUESTIONS: DUSTIN WOODS – 419-305-4891

RULES QUESTIONS: PATRICK BROWDER – 785-844-9714